



- | | |
|--------------------------------|---|
| ITEM | Hoshizaki Cubelet Ice Dispenser |
| MODEL | DCM-120KE-HC |
| POWER SUPPLY | 1 Phase 220-240V 50Hz
Capacity: 0.81kVA (3.4A) |
| AMPERAGE | Rated: 2.6A Starting: 12.3A |
| ELECTRIC CONSUMPTION | 450W (Power Factor: 72%) |
| ICE PRODUCTION PER 24h | Approx. 125kg (AT. 10°C, WT. 10°C)
Approx. 105kg (AT. 21°C, WT. 15°C)
Approx. 85kg (AT. 32°C, WT. 21°C) |
| SHAPE OF ICE | Cubelet (Compressed Flake Ice) |
| STORAGE CAPACITY | Approx. 4.0kg |
| ICE DISPENSING RATE (40g/CUP) | Approx. 165cups/30min (AT. 10°C, WT. 10°C)
Approx. 230cups/1hour(AT. 10°C, WT. 10°C)
Approx. 154cups/30min (AT. 21°C, WT. 15°C)
Approx. 209cups/1hour (AT. 21°C, WT. 15°C)
Approx. 144cups/30min (AT. 32°C, WT. 21°C)
Approx. 188cups/1hour (AT. 32°C, WT. 21°C) |
| WATER CONSUMPTION PER 24h | Approx. 0.125m ³ (AT. 10°C, WT. 10°C)
Approx. 0.105m ³ (AT. 21°C, WT. 15°C)
Approx. 0.085m ³ (AT. 32°C, WT. 21°C) |
| OUTSIDE DIMENSIONS | 350mm(W)×585mm(D)×815(~830)mm(H) |
| INSULATION FOAM BLOWING AGENT | HFC-free |
| HEAT REJECTION | 780W (AT. 32°C, WT. 21°C) |
| EXTERIOR | Stainless Steel(Side, Rear)
ABS Molding(Front, Top, Drain Pan) |
| ICE MAKING SYSTEM | Thin ice forming inside Cylinder |
| CONNECTIONS-ELECTRIC | Y-Type Connection
with CONT. Plug (L032)
with UK. Plug (L032-C101)
with CHINA Plug (L032-C301) |
| CONNECTIONS-WATER SUPPLY | Direct Connection to Water Main, Inlet G3/4(Bottom) |
| CONNECTIONS-DRAIN | Drain Hose, I.D.φ 25mm(Bottom) |
| HARVESTING SYSTEM | Direct driven Auger |
| ICE DISPENSING SYSTEM | Push Lever and Solenoid (with Select Switch)
Portion control by Dispense Switch |
| WATER DISPENSING SYSTEM | Push Lever and Water Valve (with Select Switch) |
| COMPRESSOR | Hermetic |
| CONDENSER | Fin and Tube type, Air-cooled |
| EVAPORATOR | Tube coiled around Cylinder (Solder Plated) |
| REFRIGERANT | R290/95g |
| BIN CONTROL | Mechanical Bin Control (Time Delay Controlled) |
| ICE MAKING WATER CONTROL | Float Switch and Water Valve |
| ELECTRICAL CIRCUIT PROTECTION | 10A Circuit Breaker |
| REFRIGERANT CIRCUIT PROTECTION | Compressor Internal Thermostat
Condensing Temperature detected by Thermistor(Auto-reset) |
| ICE MAKER PROTECTION | Shutdown by Microprocessor (Manual-reset) |
| WEIGHT | 56kg (Gross: 65kg) |
| PACKAGE | Carton 440mm(W) x 655mm(D)× 1026mm(H) |
| ACCESSORIES | Installation Kit, Brush |

