



# HOSHIZAKI

## IM-65NE / IM-65WLE CUBE ICE MAKER

### Product Description

The IM-65NE (air cooled) and IM-65WLE (water cooled) are self contained ice machines. These models maintain low levels of water- and energy consumption.



- A closed water circuit offers the ultimate contamination protection, by reducing the number of points at which impurities can enter the ice making process.
- Hoshizaki ice makers are micro computer controlled, controlling the ice making process to perform at its best under varying circumstances, without having to make physical adjustments.
- A stainless steel exterior with integrated door handles provides a hygienic and high quality finish.
- Foam injected polyurethane for insulation (HFC free), helps preserve the quality and consistency of the ice produced, reducing the number of production cycles.
- An easily cleanable air filter allows end users to carry out a routine cleaning schedule, extending product life expectancy and reducing the frequency and costs of maintenance call-outs.
- Removable door gaskets help prevent any heat and contamination from entering the bin as well as making your Hoshizaki product easy to clean and maintain.

### Available Models

IM-65NE (Air Cooled)
IM-65NE-25 (Air Cooled)
IM-65WLE (Water Cooled)

### Ice Cubes

Model	Size	Shape
IM-65NE / WLE	Large (Standard) 28 x 28 x 32 mm	
IM-65NE-25	Medium (25) 25 x 25 x 23 mm	

### Bins

Model	Type of Bin	Bin Capacity
IM-65NE (-25)	Self contained	26kg
IM-65WLE	Self contained	26kg

### Production

Model	Ice Production per 24h (Dimple Size)	Temperature	Ice Production per cycle	Water Consumption per 24h *
IM-65NE	Approx. 63kg (15mm) / 50kg (5mm) Approx. 56kg (15mm) / 47kg (5mm) Approx. 46kg (15mm) / 39kg (5mm)	AT.10°C, WT.10°C AT.21°C, WT.15°C AT.32°C, WT.21°C	Approx. 0,94kg / 42pcs	Approx. 0,21m <sup>3</sup> Approx. 0,14m <sup>3</sup> Approx. 0,12m <sup>3</sup>
IM-65WLE	Approx. 63kg Approx. 55kg Approx. 52kg	AT.10°C, WT.10°C AT.21°C, WT.15°C AT.32°C, WT.21°C	Approx. 0,84kg / 42pcs	Approx. 0,37m <sup>3</sup> Approx. 0,33m <sup>3</sup> Approx. 0,27m <sup>3</sup>

\*) for ice making purposes only

### Two year warranty

For more information visit our website at [www.hoshizaki-europe.com](http://www.hoshizaki-europe.com)

Hoshizaki Europe B.V. retains the right to change products and their specifications without prior notice.







# HOSHIZAKI

## IM-65NE / IM-65WLE CUBE ICE MAKER

IM-65NE



IM-65WLE



D09534 / 2011.08.24 • 97065 / 2002.03.13

Specification	IM-65NE (Air Cooled)	IM-65WLE (Water Cooled)
<b>AC Supply Voltage</b>	1 PHASE 220-240V 50Hz	1 PHASE 220-240V 50Hz
<b>Amperage</b> (AT.32°C, WT.21°C)	2.9A	2.5A
<b>Electric Consumption</b> (AT.32°C, WT.21°C)	400W	370W
<b>Exterior</b>	Stainless Steel, Galvanized Steel (Rear)	Stainless Steel, Galvanized Steel (Rear)
<b>Insulation</b>	Polyurethane Foam	Polyurethane Foam
<b>Insulation Foam Blowing Agent</b>	Water Blown	Water Blown
<b>Connections-Electric</b>	X-Type Con. (with CONT. Plug or UK Plug)	Y-Type Con. (with CONT. Plug or UK Plug)
<b>Connections-Water Supply</b>	Inlet 3/4" (connected at rear side)	Inlet 3/4" (connected at rear side)
<b>Connections-Drain</b>	Outlet 3/4" (connected at rear side)	Outlet 3/4" (connected at rear side)
<b>Ice Making System</b>	Closed Cell Type	Closed Cell Type
<b>Condenser</b>	Air-cooled, Fin and Tube type	Water-cooled, Tube in Tube type
<b>Heat Rejection</b> (AT.32°C, WT.21°C)	800W	-
<b>Refrigerant Control</b>	Capillary Tube	Capillary Tube
<b>Refrigerant Charge</b>	R134a	R134a
<b>Ice Making Control System</b>	Thermistor, Timer	Thermistor, Timer
<b>Bin Control System</b>	Microswitch with Time Delay Board	Microswitch with Time Delay Board
<b>Electrical Protection</b>	Class I Appliance, 5A Fuse	Class I Appliance, 5A Fuse
<b>Compressor Protection</b>	Auto- reset Overload Protector	Auto- reset Overload Protector
<b>Ice Maker Protection</b>	Interlock by Controller Board	Interlock by Controller Board
<b>Dimensions Product excl. Packaging</b>	633 x 506 x 840 (W x D x H, mm)	633 x 506 x 850 (W x D x H, mm)
<b>Dimensions Product incl. Packaging</b>	740 x 620 x 1035 (W x D x H, mm)	773 x 614 x 982 (W x D x H, mm)
<b>Weight Gross / Net</b>	60 kg / 53 kg	65 kg / 59 kg

Operation Requirements	
<b>Ambient Temperature</b>	1 - 40°C
<b>Water Supply Temperature</b>	5 - 35°C
<b>Water Supply Pressure</b>	0,7-7,8 bar (0,07-0,78MPa)
<b>Voltage Range</b>	Rated Voltage ± 6%

Accessories
Scoop
Leg
Installation Kit

For more information please contact your local sales office:

Hoshizaki Belgium:  
Hoshizaki Deutschland:  
Hoshizaki France:  
Hoshizaki Iberia:  
Hoshizaki Middle East:

info@hoshizaki.be  
info@hoshizaki.de  
info@hoshizaki.fr  
info@hoshizaki.es  
sales@hoshizaki.ae

Hoshizaki Nederland:  
Hoshizaki United Kingdom:  
Other countries:

sales@hoshizaki.nl  
uksales@hoshizaki.co.uk  
sales@hoshizaki.nl

[www.hoshizaki-europe.com](http://www.hoshizaki-europe.com)