







ACCESSORIES	Scoop, Leg, Installation Kit
OPERATING CONDITIONS	Ambient Temp.: 1 – 40°C, Water Supply Temp.: 5–35°C Water Supply Pressure: 0.07–0.8MPa (0.7–8bar) Voltage Range: Rated Voltage±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the ice maker properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.
3. Product Code: M115–D004

ITEM	Hoshizaki Cube Ice Maker
MODEL	IM–130WPE
POWER SUPPLY	1 PHASE 220–240V 50Hz Capacity: Min. 1.25kVA (5.3A)
AMPERAGE	Running: 3.9A Rated Motor: 3.9A Starting: 19A
ELECTRIC CONSUMPTION	Rated Motor: 530W (Power factor: 57%) (12.7kWh/24h, 13.7kWh/100kg)
ICE PRODUCTION PER 24h	Approx. 103kg (5mm)/108kg (15mm) (AT.10°C, WT.10°C) Approx. 97kg (5mm)/109kg (15mm) (AT.21°C, WT.15°C) Approx. 93kg (5mm)/99kg (15mm) (AT.32°C, WT.21°C)
POTABLE WATER CONSUMPTION PER 24h	Approx. 0.46m³ (AT. 10°C, WT. 10°C) Approx. 0.21m³ (AT. 21°C, WT. 15°C) Approx. 0.20m³ (AT. 32°C, WT. 21°C)
CONDENSER WATER CONSUMPTION PER 24h	Approx. 0.60m³ (AT. 10°C, WT. 10°C) Approx. 0.77m³ (AT. 21°C, WT. 15°C) Approx. 1.05m³ (AT. 32°C, WT. 21°C)
SHAPE OF ICE	Cube Approx. 28 x 28 x 32mm
FREEZE CYCLE TIME	Approx. 27min (AT.21°C, WT.15°C)
ICE PRODUCTION PER CYCLE	Approx. 2.0kg/80pcs. (5φ) (AT.21°C, WT.15°C)
MAX STORAGE CAPACITY	Approx. 50kg (Bin Control Setting Approx. 28kg)
OUTSIDE DIMENSIONS	704mm (W) x 506mm (D) x 1210mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear)
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Water Blown
CONNECTIONS – ELECTRIC	X–Type Con. (with CONT. Plug)
CONNECTIONS – WATER SUPPLY	Inlet G3/4 (connected at rear side)
CONNECTIONS–DRAIN	Outlet R3/4 (connected at rear side)
CONNECTIONS – COOLING WATER	Inlet Rc1/2 (connected at left side) Outlet Rc1/2 (connected at left side)
ICE MAKING SYSTEM	Cell type
HARVESTING SYSTEM	Hot Gas Defrost
COMPRESSOR	Hermetic
CONDENSER	Tube and Tube type, Water–cooled
HEAT REJECTION	1020W (880kcal/h) (AT.32°C, WT.21°C)
EVAPORATOR	Tin–plated Copper Tube on Sheet and Cells
REFRIGERANT CONTROL	Thermostatic Expansion Valve
REFRIGERANT CHARGE	R290/147g
ICE MAKING CONTROL	Thermistor, Timer
HARVESTING CONTROL	Thermistor
BIN CONTROL	Microswitch (with Time Delay)
ICE MAKING WATER CONTROL	Timer, Water Pan's Movement
ELECTRIC CIRCUIT PROTECTION	Class I Appliance, 5A Fuse
COMPRESSOR PROTECTION	Overload Protector (Auto–reset) Pressure Swiath (Auto–reset)
ICE MAKER PROTECTION	Interlock by Controller Board
WEIGHT	71kg (Gross 81kg)
PACKAGE	Carton 805mm (W) x 580mm (D) x 1375mm (H)

HOSHIZAKI CUBE ICE MAKER IM–130WPE

APPROVED S.TSUBOUCHI	CHECKED T.HUMPHREYS	DESIGNED Y.TORII	DRAWN R.UEDA	SCALE 1/20	TRIGONOMETRY
* APPROVED	* DESIGNED	* SYMBOL	**** DATE	DATE 2024.08.30	DRAWING NO. D39769
					SYMBOL △